



China's No.1 Selling Truck Brand



HOWO ELECTRIC SERIES TITAN 14FT

CHARGING YOUR BUSINESS FOWARD

Driving the future of urban transportation. Delivers power, efficiency, and zero-emission performance.



HOWO TITAN 14FT EV



HOWO Titan EV Light-Duty Truck, relying on more than 60 years of R&D and production experience of SINOTRUK. Incorporating cutting-edge technologies from both domestic and international leaders such as Weichai and CATL World-class manufacturing technology.

Key Features

- Gross Vehicle Weight:** 5.0 T
- Driving Licence:** Class 3
- Driving Range:** 250 ~ 280 km
- DC Charging Time:** 36 min (20% to 80%)
- Power Socket:** CCS2 Combo
- Cabin Width:** 2.1m for extra comfort
- Windshield:** 1.8m² extra large for improved visibility
- Entertainment System:** 12.8-inch Screen MP5

Technical Data

Product Specifications		
Key Specifications	Product Series	HOWO Titan
	Version	Wide-body standard load
	Model No	T3HE
	Cab	2,100mm Single Cab
	Overall Dimensions (mm)	5995×2200×3150
	Cargo Compartment Size (mm)	4150×2100×2100
	Wheelbase (mm)	3360
	Unladen Weight (kg)	2500
Electrical	Battery	CATL
	Battery Capacity (kWh)	86.55 Central liquid cooling
	Rated/Peak Power of Motor (kW)	70/140
Chassis	Minimum Turning Radius (mm)	6700
	Maximum Climbing Degrees	20%
	Front Axle	2T
	Rear Axle	3.5T
	Charging Power	DC - 86kW , AC - 20kW
	Tire	7.00R16 10PR
Configuration	Basic Configuration	Multi-functional steering wheel, intelligent electric power steering (IEPS), ABS (4S/4M), cab fully covered, color screen instrument, knob shifting, sport mode switch (integrated with shift lever), electronic parking brake, AUTO HOLD, central control lock and power windows + remote key, automatic headlight, PVC + fabric seat, electric variable frequency A/C, luxury rearview mirror (electrically heated), standard rear protection, wide-body cab bumper and cab sun shade, aluminum alloy rear protection.



Note: The charging time is measured with a 90 kW and above charging pile at normal temperature, and the driving range is measured under standard working conditions. In actual use, due to the influence of working condition, temperature, environment, driving habits, load, vehicle speed, charging power and other factors, the actual value may deviate from the above values, which shall be subject to the actual situation. SINOTRUK reserves the right to interpret the above values

All specifications whether in printed catalogues, prospectuses, circulars, advertisements, websites, or any other marketing materials are approximates and for illustration purposes. Steelcore Automotive Pte. Ltd. is entitled to make modifications or changes to the design of the Products without prior notice.