

MIXER SERIES

Hardox 450 In My Body **HARDOX®**
WEAR PLATE

European technology delivering
maximum payload at
lower operation costs.



TX MIXER

1 Unique blade design realizes uniform, dry, three-dimensional mixing with no segregation.

2 Good unloading speed of 0.43 m³/r.

3 Very low unloading residual rate < 0.4%.

4 Core components from renowned international brands such as PMP, TOP, ZF, Bonfiglioli.

Driving form	Engine(Ps)	Gearbox(Gears)	Axle capacity(T)	Body Volume(CBM)
6x4	400/430	9/10/12F&2R	9.5 + 2*13/2*16	6-12
8x4	430/460	9/10/12F&2R	9.5*2 + 2*13/2*16	12-16



Technical Data

Model	HOWO TXF-M 84R
Design GVW (Kg)	45,000 /51,000
Cabin	TX-F
Wheelbase (mm)	5,150 + 1,400 /5,175 + 1,350
Engine Model	MC11.43-61 /MC11.46-61
Engine Capacity (cc)	10,508
Horse Power (HP)	430 /460
Torque (Nm)	2,100/2,200 @ 1, 100-1,400 rpm
Transmission	HW25712XA(12 Forwd & 2 Rev)
Front Axle Capacity (Kg)	9500 X 2
Rear Axle Capacity (Kg)	26,000 /32,000
Frame	Double layer
Steering	R/H recirculating ball
Suspension	Parabolic 4+4+5/Multileaf 11+11+12
Brake	(F):Drum; (R):Drum + EBS+ESC+HSA
Front Axle Type	VGD95
Rear Axle Type	MCY13BGS/MCX16ZG (Hub Red)
Tyre Front (F) & Rear (R)	315/80R 22.5
Fuel Tank (L)	400
Body Type	12M ³ /14M ³ Hardox 450 Mixer



All specifications whether in printed catalogues, prospectuses, circulars, advertisements, websites, or any other marketing materials are approximates and for illustration purposes. Steelcore Automotive Pte. Ltd. is entitled to make modifications or changes to the design of the Products without prior notice.